



VIVAX
METROTECH

vLoc3-9800

Technical Specifications V1.8



Worldwide Locations

World Headquarters, United States of America

Vivax-Metrotech Corporation

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392

Tel : +1-408-734-3880

Fax : +1-408-734-1415

Website: www.vivax-metrotech.com

Email : SalesUSA@vxmt.com

Central/South America and the Caribbean

Ventas para América Latina

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392

Tel : +1-408-734-3880

Fax : +1-408-743-5597

Website: www.vivax-metrotech.com

Email : LatinSales@vxmt.com

Canada

Vivax Canada, Inc.

41 Courtland Ave Unit 8, Vaughan, ON L4K 3T3, Canada

Tel : +1-289-846-3010

Fax : +1-905-752-0214

Website: www.vivax-metrotech.ca

Email : SalesCA@vxmt.com

United Kingdom

Vivax-Metrotech Ltd.

Unit 1, B/C Polden Business Centre, Bristol Road, Bridgwater, Somerset, TA6 4AW, UK

Tel : +44(0)1793 822679

Website: www.vivax-metrotech.co.uk

Email : SalesUK@vxmt.com

France

Vivax-Metrotech SAS

Technoparc - 1 allée du Moulin Berger, 69130 Ecully, France

Tel : +33(0)4 72 53 03 03

Fax : +33(0)4 72 53 03 13

Website: www.vivax-metrotech.fr

Email : SalesFR@vxmt.com

Germany

Metrotech Vertriebs GmbH

Am steinernen Kreuz 10a
96110 Schesslitz

Tel : +49 9542 77227-43

Website: www.vivax-metrotech.de

Email : SalesEU@vxmt.com

China

Vivax-Metrotech (Shanghai) Ltd.

Building 10, Lane 1158 Zhongxin Rd.,
Songjiang District, Shanghai, China, 201615

Tel : +86-21-5109-9980

Website: www.vivax-metrotech.com

Email : SalesCN@vxmt.com.cn

A. Description and Typical Applications

Item	Parameter
Model Name	vLoc3-9800
Model Number	VX221-01
Description	Multi-purpose precision utility locator receiver
Intended Use	Locating & pinpointing the position of buried pipes, cables, and sondes

B. Characteristics

Item	Parameter
Construction	High-impact thermoplastic (ABS) injection molded housing
Weight	4.4lbs (2kg)
Dimensions	12.6in(L) x 8.6in(W) x 26.6in(H) (321mm x 219mm x 676mm)
Display Type	High-Visibility Color Display, 4.3"/10cm with 480 x 272 resolution
Receiver Antennas	<ul style="list-style-type: none"> - One Upper Horizontal Guidance Antenna - One Left Displacement Antenna - One Right Displacement Antenna - One Compass Antenna
Batteries	<ul style="list-style-type: none"> - Six x AA Alkaline batteries - Rechargeable custom Lithium-ion batteries with 100-240V AC mains charger
Battery Life	<ul style="list-style-type: none"> - Alkaline – typically 12 hours of intermittent use at 70°F (21°C) - Lithium-ion – typically 27 hours of continuous use at 70°F (21°C) <p>* With backlight activated, Battery life varies with temperature; re-charging cycles are approximately 500 times the life cycle.</p>
Environmental	IP65 and NEMA 4
External Connectors	<ul style="list-style-type: none"> - Accessory Socket – to charge the internal batteries and attach accessories - Mini USB socket for data transfer and software updates
Temperature Range	<ul style="list-style-type: none"> - Operating: -4°F to 122°F (-20°C to 50°C) - Storage: -40°F to 140°F (-40°C to 60°C)
Compliance and Approvals	<ul style="list-style-type: none"> - Complies with European standard CE (Directive 99/5/EC) <ul style="list-style-type: none"> • EN 55011 • EN 61000-4-2: A1 & A2 - Complies with FCC Rules Part 15 <ul style="list-style-type: none"> • CFR 47 part 2 • CFR 47 Part 15

	<ul style="list-style-type: none"> • EN 61000-4-3 • EN 61000-4-8: A1 • ETSI EN 300 330-2 • ETSI EN 301 489-1 • ETSI EN 301 489-3 	
Manufacturing	Designed and manufactured per ISO 9001:2015	
What's In the Box	<ul style="list-style-type: none"> - vLoc3-9800 Receiver - USB data cable - Custom Lithium-ion battery pack 	<ul style="list-style-type: none"> - 100-240V AC mains charger - Alkaline battery holder - User handbook
Compatible Accessories	<ul style="list-style-type: none"> - A-frame fault locator - Remote Antenna (Stethoscope) - Vehicle Charging Lead - External GPS Module 	<ul style="list-style-type: none"> - Range of Sondes (waterproof, self-contained transmitters for use in nonmetallic pipes & ducts)

C. Operational

Item	Parameter
Information Displayed	<p>Status Bar Information:</p> <ul style="list-style-type: none"> - Antenna configuration: Peak, Sonde, Auto or Manual - Line location - depth & current measurement - Battery condition - Speaker volume - Bluetooth - WiFi Connection - Radio link to transmitter status (if installed) <p>Locate screen (Classic display):</p> <ul style="list-style-type: none"> - Left/Right Locate Screen - Peak Locate Screen - Signal strength - numeric value - Compass: full 360°-line direction indicator - Gain level (in dB) if in Manual mode - Frequency selected - Depth and current - Warnings (if activated) - Plug and play automatic recognition of accessories - Accessory specific custom screens

	<p>Information screen:</p> <ul style="list-style-type: none"> - GPS coordinates - Signal current and depth value - Log number <p>Sonde Locate Screen:</p> <ul style="list-style-type: none"> - Peak curtain-style bar graph showing signal strength - Continuous depth reading to the sonde <p>Customer definable start-up screen</p>
<p>Locate Perspectives</p>	<ul style="list-style-type: none"> - Classic Locate - Sonde Locate Screen
<p>Configuration</p>	<ul style="list-style-type: none"> - Intuitive setup menu enables the user to configure: <ul style="list-style-type: none"> • Set up frequency selection to toggle by "f" pushbutton • Setup location mode selection to toggle by "m" pushbutton • Units of measure (feet/meter) • Language • Continuous depth/current options • Loudspeaker level • Backlight: Low, Medium, High or Auto • Bluetooth pairing • WiFi Connection • Transmitter Radio Link (Tx-Link) if installed • Auto shut down – configurable for five minutes, ten minutes or never
<p>Data Logging</p>	<ul style="list-style-type: none"> - 50 Million record storage - All parameters stored at each location, including depth, current, mode, gain setting, frequency, locate uncertainty, longitude, latitude, and height above sea level - If connected to GPS (via Bluetooth), data is also recorded with coordinates and date-time
<p>Data Transfer</p>	<p>Via the Vivax-Metrotech "MyLocator3" software application free from the Vivax-Metrotech website. Data can be saved in csv, klm, shp, txt, xls and xlsx formats. The transfer is via a USB cable connection from the locator to the host computer.</p> <p>Or</p> <ul style="list-style-type: none"> - Cellular transfer via the cloud using Vivax-Metrotech application software, VMMap
<p>Operating Frequencies</p>	<ul style="list-style-type: none"> - Configurable frequencies from 98Hz to 131kHz - Power - 50Hz and 60Hz - Radio – 10.0kHz - 22.7kHz bandwidth - Sonde - 512Hz, 640Hz, 9.82kHz, 32.8kHz, and 83.1kHz
<p>Operating Modes</p>	<ul style="list-style-type: none"> - Classic locate left/right indication

	<ul style="list-style-type: none"> - Peak Locate - Sonde locate 								
Gain Control	<p>Automatic Gain Control</p> <p>Manual gain using + or -</p> <p>One touch of + or - keys rescales to 60% of FSD</p>								
Accuracy	<table border="1"> <tr> <td>Locate pinpointing accuracy:</td> <td> <ul style="list-style-type: none"> - Up to 9ft (3m) – 3% of the depth - Over 9ft (3m) – 5% of the depth </td> </tr> <tr> <td>Depth measurement accuracy:</td> <td>+/- 5% of the depth</td> </tr> <tr> <td>Current measurement accuracy:</td> <td> <ul style="list-style-type: none"> - 3% of actual current –up to 9ft (3m) - 5% of actual current –over 9ft (3m) </td> </tr> <tr> <td>Depth range:</td> <td>- Dependent on the strength of the signal radiating to the locator</td> </tr> </table>	Locate pinpointing accuracy:	<ul style="list-style-type: none"> - Up to 9ft (3m) – 3% of the depth - Over 9ft (3m) – 5% of the depth 	Depth measurement accuracy:	+/- 5% of the depth	Current measurement accuracy:	<ul style="list-style-type: none"> - 3% of actual current –up to 9ft (3m) - 5% of actual current –over 9ft (3m) 	Depth range:	- Dependent on the strength of the signal radiating to the locator
	Locate pinpointing accuracy:	<ul style="list-style-type: none"> - Up to 9ft (3m) – 3% of the depth - Over 9ft (3m) – 5% of the depth 							
	Depth measurement accuracy:	+/- 5% of the depth							
	Current measurement accuracy:	<ul style="list-style-type: none"> - 3% of actual current –up to 9ft (3m) - 5% of actual current –over 9ft (3m) 							
	Depth range:	- Dependent on the strength of the signal radiating to the locator							
Performance rated using a single undistorted signal source									
Compatible Transmitters	Loc series, Loc3 series, VM-550FF								

D. Shipping and Packaging

Item	Parameter
Shipping Weight	10.2lbs (4.61kg)
Shipping Dimension	16.5in(L) x 11in(W) x 27.6in(H) (420mm x 280mm x 700mm)

E. Warranty

Item	Parameter
Warranty	<p>Two years</p> <p>Optional extended warranty available</p>

F. Software Updates

Item	Parameter
Software	The software can be upgraded using a PC with a USB port. Program updates & locator software updates are available via the free MyLocator3 app.

Disclaimer: Product and accessory specification and availability information are subject to change without prior notice.